



Never compromise on quality!



WEED STOP MEMBRANE

Landscaping/ Weed Suppressant Membrane

DRIVE ALIVE RANGE



Description:

A 50g landscaping and weed suppressant membrane.

Benefits:

- ◆ Durable 50 gsm.
- ◆ UV Stable.
- ◆ Non-woven.
- ◆ Superb drainage properties.
- ◆ 5 Year guarantee.

Instructions

Prepare the ground removing all weeds and rake the top soil to a smooth surface. Roll out the membrane and cut to size. Ensure a minimum of 75mm (3") overlap in large areas where multiple strips are required. Secure the membrane and overlaps with ground pegs at regular intervals. When planting; cut a cross in the membrane and pin back in place. Cover with at least 50mm (2") of bark, mulch of gravel. The fabric can be cut around existing trees, plants or hedges etc.

Limitations

WEED STOP MEMBRANE should not be used under patios, driveways or block paving. **WEED STOP** should not be used under trafficked areas such as gravel paths.

Roll Size

1M wide by 15M long or 2M x 25M long.

Colour

Black fabric.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

| | |
|----------------------------|--------------------|
| Weight | 50g/m ² |
| MD Tensile Strength N/5cm | 145 |
| CD Tensile Strength N/5 cm | 95 |
| MD Elongation | 110% |
| CD Elongation | 120% |

Product Details:

| | | |
|-----------------|---------------|--------------|
| Code: | BDWBM15 | BDWBM25 |
| Colour: | Black | Black |
| Size: | 1M x 15M | 2M x 25M |
| Barcode: | 5060021369024 | 506002136903 |



Part of the Bond It Drive Alive Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V2 24/11/17
Supercedes: V1 04/03/11