

Product Specification of Larchfield

For elegance and simplicity, the Larchfield Original Paving Block has the classic rectangular shape allowing various installation designs that will remain stylish and attractive for years to come.

Thickness: 50mm, 60mm or 80mm depending on trafficking requirement

Use: Roads & Footpaths— domestic & commercial


Laying Patterns: Suitable for various laying patterns including Herringbone, Stretcher bond and Basket Weave

Chamfer: Each brick has a pencil line chamfer on all top surfaces

Spacing Nibs: 1.5mm nibs

Finishes & Colour: Standard finish with 9 colour options

Kerbs: Complimentary kerb range available



Product	Brick Size mm	Colours	No. per Sq.m	No. per Pack	M ² per Slice	Pack Size Sq.m	Pack Weight	No. Packs per Arctic	Sq.m per Arctic
50mm	200 X 100 X 50	Available in all colours	50	180	1.6	9.6	1160	24	230.4
60mm	200 X 100 X 60	Available in all colours	50	384	1.28	7.68	1100	25	200
80mm	200 X 100 X 80	Made to Order	50	480	n/a	9.6	1730	16	153.6

Raw Materials: Sand, Stone, Cement, Pigment

Manufacturing Process: Hydraulically Pressed

Manufacturing Standards: Manufactured to BS EN 1338

Quality Systems: All products undergo testing to standards of EN ISO 9001 and are covered by CE certification.

Application: Please refer to Health & Safety data sheets

Installation: Installed to BS 7533-3

Performance Criteria: Strength:>3.6MPa or 250N/mm

Barleystone Paving, Taghart
South, Shercock,
Co. Cavan, A81 D667