bond it

Never compromise on quality!

MADE IN THE UK

HEAVY DUTY FLOOR PAINT

Alkyd Based, Hard Wearing, Satin Finish Floor Paint



BUILDERS COMPLETE RANGE

Description:

A high solids, low viscosity, hard wearing, heavy duty alkyd formulation floor paint for use on concrete, wood, brick and stone. Dries to a satin finish. For interior use only.

Uses

Designed to give a hard wearing, easy clean finish to concrete, stone, brick and wooden floors subject to light to medium traffic including fork lift trucks and scissor lifts, etc. Suitable for use internally on garage floors, warehouses, workshops, factories, storerooms, pedestrian walkways and is designed to give enhanced durability, abrasion resistance and good resistance to dilute acids/alkalis and oils including brake fluid, engine cleaners, screen wash, anti-freeze, power steering fluid, diesel and sump oil.

Surface Preparation

All surfaces must be clean of any contaminants such as dust, oil, etc. and dry (to the touch). Remove any loose or flaking material with a scraper and stiff brush to expose a smooth debris free surface. Remove any moss, mould or lichens with Bond It MOULD-STOP or ORGANIC CLEANER. Chemically or mechanically hardened floors may require abrasion prior to use. If in doubt test a small area prior to full application.



Application

This product is ready to use product and does not require diluting. Apply using brush or roller to give even coat, 2 coats are usually required. Bond It **FLOOR PAINT** is touch dry within 2-3 hours depending on ambient temperatures, leave 16 to 24 hours between each coat. Clean tools and brushes with white spirit. Cured paint can be removed using xylene (paint stripper). Priming isn't usually required, but if necessary apply a coat of 1 part Bond It WHITE SPIRIT to 4 parts paint and allow to dry before proceeding.



Limitations

New concrete must be a minimum of 6 months old before painting. Do not use on concrete floors with a moisture level reading above 18%, that do not have a waterproof membrane or that contain a dust suppressing additive. Only suitable for light to medium traffic, for areas subject to heavy traffic or constant use, an epoxy based paint would be recommended. Do not traffic until fully cured. Not suitable for use on bitumen or asphalt. If in doubt about any application please contact our technical department.

Coverage

Approximately 15m^2 per litre (1 coat).

Container Size

5L metal tins.

Colour

Available in dark grey, light grey and red and gives a satin finish once dried.

Limitations

New concrete must be a minimum of 6 months old before painting. Do not use on concrete floors with a moisture level reading above 18%, that do not have a waterproof membrane or that contain a dust suppressing additive. Only suitable for light to medium traffic, for areas subject to heavy traffic or constant use, an epoxy based paint would be recommended. Do not traffic until fully cured. Not suitable for use on bitumen or asphalt. If in doubt about any application please contact our technical department

Shelf Life

24 months from date of manufacture when stored in sealed tins.

Storage Conditions

Store in cool, dry conditions in original sealed container between 5 and 25°C. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Flammability	Flammable
Film Thickness (dry)	Min 25 - max 40 microns
Drying Time	Touch dry 2-3 hrs; 16-24 hrs between coats
UFI	VX00-F08Y-6003-PXS2

Product Details:

Colour:	Brick Red (Satin)	Grey (Satin)	Light Grey (Satin)
Code:	BDFPR5	BDFPGR5	BDFPLG5
Size:	5L	5L	5L
Barcode:	5056437400499	5056437400505	5056437400604



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.

Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT
Head Office: *Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.*
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

V2 16/02/21
Supercedes: V1 24/05/17