Data Sheet | Item Number: 887-1046

Set; 221 Series

https://www.wago.com/887-1046



This item includes:

Item No.: 221-412	Item No.: 221-413	Item No.: 221-415	15
Splicing connector with levers; for all conductor types; max. 4 mm²; 2-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	Splicing connector with levers; for all conductor types; max. 4 mm²; 3-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	Splicing connector with levers; for all conductor types; max. 4 mm²; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent	

Notes

General safety instructions	**NOTICE: Observe installation and safety instructions!** • **Only to be used by electricians!** • Do not work under voltage/load! • Use only for proper use! • Observe national regulations/standards/guidelines! • Observe technical specifications for the products! • Observe the number of permissible potentials! • Do not use damaged/dirty components! • Observe conductor types, cross-sections and strip lengths! • Insert conductor until it hits the product's backstop! • Use original accessories! **To be sold only with installation instructions!**

Physical data

Width	180 mm / 7.087 inches
Height	40 mm / 1.575 inches
Depth	150 mm / 5.906 inches

Material data

Note (material data)	Information on material specifications can be found here
Fire load	4.615 MJ
Weight	341 g

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
GTIN	4066966424751

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 887-1046