

UK CE LIN THE

Never compromise on quality!

### POWDERED CEMENT COLOUR

### Permanent Powder Colourant For Cement

**Technical Data Sheet** 



**BUILDERS COMPLETE RANGE** 

CLASS **EN12878** 

### **Description:**

A easily dispersed premium grade permanent colourant for mortars and renderings. Conforms to FN12878.

### CHLORIDE CONTENT CATEGORY

### **Benefits:**

- Formulated for easy incorporation into a mix.
- High quality non-fading, light-fast pigments.
- No loss in performance when used as directed, see limitations.

### **Uses**

For permanently colouring cements, mortars, concretes and renderings. Suitable for use in conjunction with other admixtures, e.g. Bond It LIQUID MORTAR PLASTICISER, INTEGRAL WATERPROOFER, FROSTPROOFER AND HARDENER and SBR ADMIXTURE.

# FROST FOR CELL COLUMN TO THE CEL

### **Application**

### Pre-mix Bond It POWDERED CEMENT

**COLOUR** into the dry sand/cement mixture either by hand or machine, before adding the gauging water. To ensure you are able to match the colour, always weigh the cement dye and the cement, do not gauge by volume. For lighter shades reduce the amount of dye added. It is recommended to prepare a test sample first to determine amount of cement dye required. Colour will become lighter as cement dries. Pictures showing approximate shades are available on request from technical department.

### Limitations

Do not exceed 5Kgs of dye per 50Kgs of cement as the quality of the mortar could be compromised.

### Coverage

Maximum 5Kgs dye to 2 x 25Kgs cement.

### **Container Size**

1Kg composite tins.

### **Colour**

Available in black, brown, red and yellow.

### **Shelf Life**

5 years from date of manufacture when stored in unopened tins.

### **Storage Conditions**

Store in cool, dry conditions between +5 and +25°C. Protect from frost.

### **Disposal of Containers**

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

### **Health & Safety**

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



# Appearance Fine coloured powder Flammability Non-flammable pH N/A Solubility in Water: Insoluble Composition Mixture based on inorganic metallic oxides

### **Product / Order Details:**

Code	Colour	Size	Barcode
BDH060BL	Black	1Kg	5060021361233
BDH060BR	Brown	1Kg	5060021361240
BDH060R	Red	1Kg	5060021361257
BDH060Y	Yellow	1Kg	5060021361264



13

2797 CPR 582453

UK CA

3 0086 CPR 749

2

### **BOND IT**

G16 River Bank Way, Elland. HX5 9DN. UK

### EN12878

Pigments for the colouring of building materials based on cement and/or lime.

**Chemical Composition** Synthetic iron

oxide

Setting Time Pass

Compressive Strength Category A

Soluble Chloride Content Category A

Total Chlorine Content Category A

Water Soluble Content Category A

**Loss Of Ignition** Pass

**Emission Of Radioactivity** 

**And Release Of** 

Dangerous Substance NPD







The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the





**Head Office:** Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



products for a particular purpose.

**Rev: V4 13/10/22** Supercedes: V3 20/5/20