



Never compromise on quality!



# SBR ADMIXTURE

## Mortar/ Rendering Admixture And Bonding Agent



BUILDERS COMPLETE RANGE

### Description:

*A premium grade SBR designed to give concrete floors and cement renders abrasion, chemical and water resistance. Bond It SBR also shows improved performance as a key coat adhesive compared to non SBR bonding agents.*

### Uses

For improving a mortar's, render's or floor screed's abrasion and chemical resistance. Providing protection during continued or intermittent water contact suitable for both external or internal use application. Key coat applications to substrates with a low porosity. For repair patching of concrete and cement screeds, to improve adhesion and flexibility of screeds.

### Application

All surfaces should be free from laitance, oil, grease and standing water. Unsound surfaces should be scabbled down to a solid base material. Stir before use.

**Key Coat:** Mix 1 part Bond It **SBR** to 2 parts cement by volume and adjust to brushable consistency with water. Mix only enough to use within the hour. Brush thoroughly into a clean dust free substrate, whilst still wet overcoat with the floor or render mix.

**Damp-proofing:** Mix the same formulation as in the key coat and apply the first coat with vigorous brush strokes. Allow to touch dry then apply a second coat at 90° to the first and allow 48 hours to dry. Apply the third coat at 90° to the second coat and while still wet apply the render.

**Renderings/Mortars:** Prepare the substrate with the key coat first for best results. Mix sand/cement mortar/render and add 5-7.5 litres Bond It **SBR** per 25Kgs cement, reducing the amount of gauging water accordingly. Apply at least 6mm thick. Two coats are recommended.

**Granolithic Floorings:** Prepare the substance with the key coat first for best results. Mix cement: sand: 3mm granite flooring chips 1: 1½: 1½ Use 5L Bond It **SBR** to each 25Kg of cement, for floors up to 25mm thick. For floors greater than 25mm use 2.5 litres Bond It **SBR** and add water accordingly to produce a semi-dry mix.

**Patching Concrete:** Use the key coat and use a 3:1 render mix feathering lightly.

### Limitations

Protect from freezing. Do not use with cements other than OPC without first contacting the cement supplier. Do not use chloride

based frost proofers with Bond It **SBR**. Do not over mix mortar/render. Do not use when air or surface temperatures are below +3°C.

### Cleaning of Tools

Rinse equipment after use with plenty of clean water.

### Coverage

**Flooring:** 5 litres **SBR** for every 25Kgs cement.

**Mortar/Rendering:** 5-7.5 litres **SBR** for every 25Kgs cement.

**Key Coat:** 5 litres **SBR** per 30m<sup>2</sup> depending on porosity.

### Container Size

5L, 25L plastic bottles. 200L also available on request.

### Colour

White liquid.

### Shelf Life

2 years from date of manufacture when stored in sealed bottles.

### Storage Conditions

Store in cool, dry conditions in a sealed container between +5 & +30°C and protect from frost.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.**

## Specification Summary

Appearance	Milky white liquid capable of florescence
Flammability	Non-flammable
pH	approximately 9.5
Solubility in Water	Soluble
Boiling Point	+100°C

## Product Details:

<b>Colour:</b>	White	White	White
<b>Code:</b>	BDH040	BDH041	BDH042
<b>Size:</b>	5L	25L	200L
<b>Barcode:</b>	5060021361196	5060021361202	5060021364234



Part of the Bond It Builders Complete Range

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Certificate Number:  
6152  
ISO 9001; ISO 14001;  
ISO 45001



SCAN ME AND GET THE BOND IT APP

**BOND IT**  
**Head Office:** Unit G16 River Bank Way, Lowfields Business Park,  
 Elland, West Yorkshire HX5 9DN.  
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
 Email: [salesuk@bonditgroup.com](mailto:salesuk@bonditgroup.com) Website: [www.bonditgroup.com](http://www.bonditgroup.com)



**V5 01/07/22**  
 Supersedes: V4 20/05/20