

TCB

### Thin Coat Angle Bead

*Thin Coat Bead (25mm wing, 3mm plaster depth)*


- *Designed for use with one coat plaster work down to a 3mm finish.*
- *Perforated wings to provide an excellent plastering key.*

#### **Installation:**

*Installation usually achieved by pressing the wings firmly into plaster dabs placed at approximately 600mm centres both sides of the aris. The wings may alternatively be embedded into the first coat of plaster for normal two-coat work.*

*Beads may be cut to size as required by using a hacksaw and snips. Beads should be stored off the ground and in dry conditions during site work.*

UK  
CA



**TCB**  
**Thin Coat Angle Bead****Technical Data**

## TCB - Dimensions

References	Material	Length
TCB2404	Galvanised	2.4m
TCB3004	Galvanised	3.0m

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

TCB  
**Thin Coat Angle Bead**

Copyright by Simpson Strong-Tie®  
Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

2023-08-01



[www.strongtie.co.uk](http://www.strongtie.co.uk)